New upgrade emulsion spraying machine

Powerful / spreading uniformity / stable performance / easy to carry

Applicable: Asphalt pavement maintenance, roof waterproof; bridge waterproof; under the sealed construction; manhole maintenance

Basic Overview



Performance Advantage



Small size, light weight

Small size, light weight, easy to carry.



Spread evenly

Spread evenly, the amount of 22L per minute spread.



Honda engine

Use of Honda 160 engine drive, powerful, overall performance of the machine is stable.



safe and efficient

Meeting the requirements of road maintenance construction operations, a large area of construction, bitumen barrels with filter device to prevent blocking the tube.

Technical Data

Modle	FND-RP160
Weight	64 KG
Dimensions(mm)	1085 X 530 X 750
Reted power	3.6 KW （4.9PS）
generator	Honda GX160
Fuel	Unleaded gasoline
Oil box capacity	3.1 L
Lubrication	10W - 30(above SE level)
Lubrication capacity	0.58 L
Starting method	Kick-type
Spray ablity	22 L/min
Spray pressure	1MPa
Nozzle	1
Pump	Geared
Clean pump	Diesel
Whole clean	Polyethylene（20L）

Product Display





FND www.fanuode.net
SuZhou FaNuoDe Engineering Machinery Co.,Ltd.
No. 68, Fuxian, 227 Highway Road, Songling Town, Wujiang District, Suzhou City, jiangsu Province
Hotline：（+86）512-62538115　13771800605